

TIO BAR STOOL

Tio Bar Stool
TI-03 02 00

Seat Height	650 mm
-------------	--------

Color	Black - RAL 9005
	Beige Red - RAL 3012
	Blue Green - RAL 6004
	Brown Beige - RAL 1011
	Ivory - RAL 1015
	Pale Brown - RAL 8025
	Pastel Turquoise - RAL 6034
	Stone Grey - RAL 7030
	White - RAL 9003
Wine Red - RAL	

Specifications

Width: 520 mm

Depth: 500 mm

Weight: 6 kg

Height: 845 mm

Seat Height: 650 mm

Information

Year: 2009



Description

Stackable bar stool for indoor as well as outdoor use. Galvanized metal wire covered with a polyester powder coat, available in ten colours.

Lead time 6 weeks.

Instructions

For metal surfaces: Rinse with large quantities of water. Clean with wetting agent solution and use a sponge or soft cloth. Post-rinsing and drying. Specific instructions based on type of soiling: Greasy film can be removed with a concentrated wetting agent solution, alcohol or surfactant, after allowing the solution some time to break down the film before removing. Unidentifiable, stubborn dirt can be treated with facade cleaner (e.g., Ambruch2 www.ambruch.de) or Power Wipes www.interflon.net. Note: The specific methods listed here should be tested accordingly for possible damage to the surface.

TIO BAR STOOL

Tio Bar Stool
TI-04 04 00

Seat Height 750 mm

Color

- Black - RAL 9005
- Beige Red - RAL 3012
- Blue Green - RAL 6004
- Brown Beige - RAL 1011
- Ivory - RAL 1015
- Pale Brown - RAL 8025
- Pastel Turquoise - RAL 6034
- Stone Grey - RAL 7030
- White - RAL 9003
- Wine Red - RAL

Specifications

Width: 520 mm

Depth: 500 mm

Weight: 6 kg

Height: 945 mm

Seat Height: 750 mm

Information

Year: 2009



Product image may differ from your selection.

Description

Stackable bar stool for indoor as well as outdoor use. Galvanized metal wire covered with a polyester powder coat, available in ten colours.

Lead time 6 weeks.

Instructions

For metal surfaces: Rinse with large quantities of water. Clean with wetting agent solution and use a sponge or soft cloth. Post-rinsing and drying. Specific instructions based on type of soiling: Greasy film can be removed with a concentrated wetting agent solution, alcohol or surfactant, after allowing the solution some time to break down the film before removing. Unidentifiable, stubborn dirt can be treated with facade cleaner (e.g., Ambruch2 www.ambruch.de) or Power Wipes www.interflon.net. Note: The specific methods listed here should be tested accordingly for possible damage to the surface.