MEGA 2 SEATER SOFA

Mega 2 Seater Sofa MG-02 22 250

Color

Black - RAL 9005 Stone Grey - RAL 7030 White - RAL 9003



Specifications

Width: 1800 mm

Depth: 900 mm

Weight: 55 kg

Height: 790 mm

Seat Height: 420 mm

Information



Description

Designer Chris Martin saw a rack of freshly baked loaves in a bakery and found something instantly appealing about the risen bread against the metal wires. The idea became a sofa with thin steel tube side panels that enclose and lift the plump cushions. Mega offers superb comfort and sculptural expression to offices, hotels and homes.

Lead time 6 weeks.

Instructions

For cleaning of metal surfaces: Rinse with large quantities of water. Clean with wetting agent solution and use a sponge or soft cloth. Post-rinsing and drying. Specific instructions based on type of soiling: Greasy film can be removed with a concentrated wetting agent solution, alcohol or surfactant, after allowing the solution some time to break down the film before removing. Unidentifiable, stubborn dirt can be treated with facade cleaner (e.g., Ambruch2 www. ambruch.de) or Power Wipes www.interflon. net. Note: Special care should be taken with coatings that have a metallic, pearl mica or matte effect. The specific methods listed here should be tested accordingly for possible damage to the surface. For cleaning of the fabric/leather, see instructions related to the specific fabric/leather in use.

MEGA 3 SEATER SOFA

Mega 3 Seater Sofa

MG-01 22 250 €3589 Please note - prices do not include VAT.

Color

Black - RAL 9005 Stone Grey - RAL 7030 White - RAL 9003

Available in a variety of fabrics.

Specifications

Width: 2300 mm

Depth: 900 mm

Weight: 60 kg

Height: 790 mm

Seat Height: 420 mm

Information

Year: 2012



Description

Designer Chris Martin saw a rack of freshly baked loaves in a bakery and found something instantly appealing about the risen bread against the metal wires. The idea became a sofa with thin steel tube side panels that enclose and lift the plump cushions. Mega offers superb comfort and sculptural expression to offices, hotels and homes.

Lead time 6 weeks.

Instructions

For cleaning of metal surfaces: Rinse with large quantities of water. Clean with wetting agent solution and use a sponge or soft cloth. Post-rinsing and drying. Specific instructions based on type of soiling: Greasy film can be removed with a concentrated wetting agent solution, alcohol or surfactant, after allowing the solution some time to break down the film before removing. Unidentifiable, stubborn dirt can be treated with facade cleaner (e.g., Ambruch2 www. ambruch.de) or Power Wipes www.interflon. net. Note: Special care should be taken with coatings that have a metallic, pearl mica or matte effect. The specific methods listed here should be tested accordingly for possible damage to the surface. For cleaning of the fabric/leather, see instructions related to the specific fabric/leather in use.

Instructions for Fabric

Vacuum regularly. Professionally dry clean or wipe clean with a damp cloth.